

PSC Linux Sensor version 2.2.0 is a release for select distributions of Linux. See [the Supported Operating Systems](#) Section or the [PSC Linux Sensor Support](#) page to view the supported Linux distributions.

New features

This section lists features that are introduced in the PSC Linux 2.2.0 sensor.

- Live Response on Ubuntu
- Live Response on Amazon Linux
- Live Response on SUSE

Live Response for Linux

The 2.2.0 PSC Linux sensor adds Live Response to SUSE, Ubuntu and Amazon Linux. Live Response is also supported on RHEL 6/7 and CentOS 6/7.



Click this icon next to the device name to initiate a Live Response session. There is a known issue where the icon is visible even if Live Response is not enabled for that device. A policy must be assigned to each sensor to use Live Response.

See the in-product User Guide and the [Live Response Blue Team Handbook](#) for more information about using Live Response.

Attended and Command Line Installation

For attended installs, an `install.sh` script is provided to input the company code for registration purposes. Command Line Installation is also supported via the use of the native RPM installer (assuming prerequisite steps are taken). See the [PSC Sensor Installation Guide](#) for instructions.

Known differences between Linux and other operating systems

The **User** field on the **Endpoints** page is typically populated by the email address of the user who installed the sensor on the endpoint. We've intentionally left this field blank for Linux

Carbon Black.

sensors because there can be multiple logged-in users and multiple simultaneous desktop users.

Known issues

Issue ID	Description
CB-17911	The sensor does not support uninstall from the PSC cloud. To uninstall, issue the following commands: For CentOS, RHEL, SUSE or Amazon Linux: <code>rpm -e cb-psc-sensor</code> For Ubuntu: <code>dpkg --purge cb-psc-sensor</code> Note: The agent will still be listed in the Registered Devices list on the backend after running the command unless the user chooses <i>Take Action</i> -> <i>Uninstall</i>
CB-22784	The sensor only supports unauthenticated proxies. Support for authenticated proxies will be available in a future release.
DSER-14548	Live Response "Go Live" Icon always shows for Linux sensors. A policy must be assigned to each sensor to use Live Response.
CB-24193	The sensor does not automatically support port 54443 if port 443 fails. The following workaround can be applied in order to use port 54443. <ol style="list-style-type: none">1. On installation, call <code>./install.sh</code> without arguments The agent will be installed, but not started.2. Edit <code>/var/opt/carbonblack/psc/cfg.ini</code> as follows:<pre>[customer] PemFile=/var/opt/carbonblack/psc/cloud.pem CompanyCode=<8 char code for org> BackendServer=https://dev-prod<XX>.conferdeploy.net:54443</pre>

Supported Operating Systems

This section lists the operating systems supported by the PSC Linux 2.2.0 sensor.

- SLES 12 SP2
- SLES 12 SP3
- SLES 12 SP4
- SLES 15
- OpenSUSE Leap 42.2

Carbon Black.

- OpenSUSE Leap 42.3
- OpenSUSE Leap 15
- Ubuntu 16.04 LTS
- Ubuntu 18.04 LTS
- Ubuntu 18.10
- Amazon Linux 2
- RHEL 6 (supported in 2.1.0 release)
- RHEL 7 (supported in 2.1.0 release)
- CentOS 6 (supported in 2.1.0 release)
- CentOS 7 (supported in 2.1.0 release)