Summary

CB Response 6.3.1 is a maintenance release of the CB Response server and console. 6.3.1 release contains high severity bug fixes.

This release includes the following components:

- Server version 6.3.1.190402
 Release Notes: (this document)
- Windows Sensor version 6.1.9.181012
 Release Notes
- MacOS Sensor version 6.2.4.190328
 Release Notes
- Linux Sensor version 6.1.10.10169
 Release Notes

Each release of CB Response software is cumulative and includes changes and fixes from all previous releases.

Corrective Content

- 1. CB diagnostics data will be generated without timing out. [CB-25604]
- 2. The amount of time for sensor status to switch from "online" to "offline" and vice versa can be configured in cb.conf via SensorCheckinOnlineIntervalMin=<value>. [CB-25430]

Document Contents

This document provides information for users who are upgrading to CB Response Server version 6.3.1 from previous versions, and for users who are new to CB Response. The key information specific to this release is provided in the following major sections:

- Preparing for Server Installation or Upgrade Describes requirements to meet and key information needed before beginning the installation process for the CB Response server.
- **New features** Provides a quick reference to the new and modified features that are introduced with this version.
- **Corrective content** Describes issues that are resolved by this release as well as more general improvements in performance or behavior.
- Known issues and limitations Describes known issues or anomalies in this version.

Copyright © 2011–2019 Carbon Black, Inc. All rights reserved. This product may be covered under one or more patents pending. CB Response is a registered trademark of Carbon Black, Inc. in the United States and other countries. Any other trademarks and product names used herein may be the trademarks of their respective owners.

Additional Documentation

This document supplements other Carbon Black documentation. <u>Click here</u> to search the full library of CB Response user documentation on the Carbon Black User eXchange.

Technical Support

CB Response server and sensor update releases are covered under the Customer Maintenance Agreement. Technical Support is available to assist with any issues that might develop during the installation or upgrade process. Our Professional Services organization is also available to help ensure a smooth and efficient upgrade or installation.

Use one of the following channels to request support or ask support questions:

• Web: <u>User eXchange</u>

• Email: support@carbonblack.com

Phone: 877.248.9098Fax: 617.393.7499

Reporting Problems

When contacting Carbon Black Technical Support, provide the following required information:

- Contact: Your name, company name, telephone number, and email address
- **Product version**: Product name (CB Response server and sensor version)
- **Hardware configuration:** Hardware configuration of the CB Response server (processor, memory, and RAM)
- **Document version:** For documentation issues, specify the version and/or date of the manual or document you are using
- **Problem:** Action causing the problem, the error message returned, and event log output (as appropriate)
- **Problem severity:** Critical, serious, minor, or enhancement request

Note: Before performing an upgrade, Carbon Black recommends reviewing content on the User eXchange for the latest information that supplements the information that is contained in this document.

[On-Prem Only] Preparing for Server Installation or Upgrade

This section describes the requirements and key information that is needed before beginning the installation process for the CB Response server. All on-premises users, whether upgrading or installing a new server, should review this section before proceeding. Next, see the appropriate section of the CB Response Server/Cluster Management Guide version 6.3.0 for specific installation instructions for your situation:

- To install a new CB Response server, see "Installing the CB Response Server".
- To upgrade an existing CB Response server, see "Upgrading the CB Response Server".

Yum URLs

CB Response Server software packages are maintained at the Carbon Black yum repository (yum.distro.carbonblack.io). **The links will not work until the on-prem GA date**.

Our yum links for the CB Response server have changed. The following links make use of variables to ensure that you install the correct version of CB Response, based on your machine's OS version and architecture.

Use caution when pointing to the yum repository. Different versions of the product are available on different branches as follows:

• **Specific version:** The 6.3.1 version of server and Unified View is available from the Carbon Black yum repository specified in the following base URLs:

Server:

baseurl=https://yum.distro.carbonblack.io/enterprise/6.3.1-1/\$releasever/\$base
arch/

This link is available as long as this specific release is available. It can be used even after later versions have been released, and it can be useful if you want to add servers to your environment while maintaining the same version you already have installed.

 Latest version: The latest supported version of the CB Response server and Unified View is available from the Carbon Black yum repository specified in the following base URLs:

Server:

baseurl=

https://yum.distro.carbonblack.io/enterprise/stable/\$releasever/\$basearch/

This will point to version 6.3.1-1 until a newer release becomes available, at which point it will automatically point to the newer release.

Note: Communication with this repository is over HTTPS and requires the presence of appropriate SSL keys and certificates. During the CB Response server install or upgrade process, other core CentOS packages can be installed to meet various dependencies. The standard mode of operation for the yum package manager in CentOS is to first retrieve a list of available mirror servers from http://mirror.centos.org:80 and then select one of those mirrors to download the actual dependency packages. If your CB Response server is installed behind a firewall that blocks access to the outside, it is up to the local network and system administrators to ensure that the host machine can communicate with standard CentOS yum repositories.

[On-Prem Only] System Requirements

Operating system support for the server and sensors are listed here for your convenience. The document *CB Response Operating Environment Requirements* document describes the full hardware and software platform requirements for the CB Response server and provides the current requirements for systems that are running the sensor. This document is available on the Carbon Black User eXchange.

Both upgrade and new customers should be sure to meet all of the requirements specified here and in the Operating Environment Requirements before proceeding.

Server / Console Operating Systems

Note: For best performance, Carbon Black recommends running the latest supported software versions.

- CentOS 6.7-6.10 (64-bit)
- CentOS 7.3-7.6 (64-bit)
- Red Hat Enterprise Linux (RHEL) 6.7-6.10 (64-bit)
- Red Hat Enterprise Linux (RHEL) 7.3-7.6 (64-bit)

Installation and testing are performed on default install using the 'minimal' distribution and the distribution's official package repositories. Customized Linux installations must be individually evaluated.

Sensor Operating Systems (for Endpoints and Servers)

For the most up-to-date list of supported operating systems for CB Response sensors (and all CB endpoint products), see the following page in the Carbon Black User eXchange:

https://community.carbonblack.com/docs/DOC-7991

Note: Non-RHEL/CentOS distributions or modified RHEL/CentOS environments (those built on the RHEL platform) are not supported.

Configure Sensor Updates Before Upgrading Server

CB Response 6.3.1 comes with updated sensor versions. Servers and sensors can be upgraded independently, and sensors can be upgraded by sensor groups instead of all at once.

Decide if you would like the new sensor to be deployed immediately to existing sensor installations, or if you want to install only the server updates first. Carbon Black recommends a gradual upgrade of sensors to avoid any unacceptable impact on network and server

performance and strongly recommends that you review your Sensor group Upgrade Policies before upgrading your server to avoid inadvertently upgrading all sensors at the same time. For detailed information on Sensor Group Upgrade Policy, see the Sensor Group section of the *CB Response User Guide* for version 6.3.1.

To configure deployment of new sensors via the CB Response web UI, follow the instructions in the CB Response User Guide.

Known Issues

- 1. Invalid query when creating a watchlist from a Threat Feed. When creating a watchlist from a Threat Feed, CB Response incorrectly creates the query and the watchlist will not run and creates an error. To see if your watchlist that was created from a threat feed has formed an error, check the Watchlist page for the status. As a workaround, the CB Response Team suggests clicking on the Search Binaries or Search Process hyperlinks on the Threat Feed and then Add/Create Watchlist action from the search page.
- 2. If the browser timezone is different from the server timezone, you might notice a discrepancy in the last check-in time shown for Sensors. [CB-20076]
- 3. The CSV export of the user activity audit is malformed in certain cases. [CB-18936]
- 4. The CSV Export of 'Recently Observed Hosts' has no header row. [CB-18927]
- 5. When using a custom email server, you cannot enable or disable Alliance Sharing. The workaround for this is to disable the custom email server, make the change, then re-enable customer email server. [CB-20565]
- 6. For sensor upgrades to work properly, you might need to configure McAfee EPO to exclude c:\windows\carbonblack\cb.exe from its "Prevent creation of new executable files in the Windows folder" option. [CB-7061]
- 7. Command Line query hyperlink in Process Analyse page is not working if the command line begins with a leading forward '/'. Leading forward '/' is not tokenized, and is treated as a command line switch. Alternatively use cmdline:usr/sbin/netbiosd or cmdline:"usr/sbin/netbiosd" in the search to get results. [CB-25072]