

PSC Linux Sensor version 2.4.0 release adds Live Query capabilities and Port 5443 Support. See the [PSC Linux Sensor Support](#) page to view the supported Linux distributions. Live Query is supported on all these distributions.

## New features

---

This section lists features that are introduced in the PSC Linux 2.4.0 sensor.

- Live Query
- Port 54443 Support

### Live Query for Linux

Live Query is one of the main functionalities of Carbon Black's LiveOps product. Live Query allows you to ask questions to your endpoint in real-time. To learn more about how to use Live Query please visit [our community](#). Refer to the following [UEX page](#) for a list of suggested queries (includes Linux, Mac and Windows).

### Port 54443 Support

The agent can now communicate with the Predictive Security Cloud over port 54443 if port 443 is unavailable.

### Attended and Command Line Installation

For attended installs, an `install.sh` script is provided to input the company code for registration purposes. Command Line Installation is also supported via the use of the native RPM installer (assuming prerequisite steps are taken). See the [PSC Sensor Installation Guide](#) for instructions.

### Known differences between Linux and other operating systems

The **User** field on the **Endpoints** page is typically populated by the email address of the user who installed the sensor on the endpoint. We've intentionally left this field blank for Linux sensors because there can be multiple logged-in users and multiple simultaneous desktop users.

# Carbon Black.

## Known issues

Issue ID	Description
CB-17911	<p>The sensor does not support uninstall from the PSC cloud. To uninstall, issue the following commands:</p> <p>For CentOS, RHEL, SUSE or Amazon Linux: <code>rpm -e cb-psc-sensor</code> For Ubuntu: <code>dpkg --purge cb-psc-sensor</code></p> <p><b>Note:</b> The agent will still be listed in the Registered Devices list on the backend after running the command unless the user chooses <b>Take Action &gt; Uninstall</b></p>
CB-22784	<p>The sensor only supports unauthenticated proxies. Support for authenticated proxies will be available in a future release.</p>
CB-25700	<p>Live Response <b>Go Live</b> icon always shows for Linux sensors. A policy must be assigned to each sensor to use Live Response.</p>